BUILT BY **THE BEST** TO WITHSTAND **THE WORST.**

Product **data sheet**



SOS400MK2

Typical use:

ing line

Ports, shore lines and Marinas
For the storage of 1 x 762mm lifebuoy and throw-

Description:

This fully enclosed design was created with the assistance of the RNLI. It provides excellent protection of the lifebuoy and line from both rain and UV degradation. The round design with lifebuoy symbol makes it very easy to identify in an emergency. The double doors are opened using one hand and can be fitted with an anti-tamper seal to deter theft. The labelling of the housing is integrated into the moulding and so will not peel off.

Standard specification:

Dimensions (mm)

Height x width x depth: 930 x 918 x 210

Height including poles 1930

Weight Kg: 10Kg

Material specification:

Colour: Orange

Material:

UV Stabilized rotationally moulded pol-

yethylene

Optional Extras:

L762 Lifebuoy

LTL762 30M throwing line in white PVC container



BUILT BY **THE BEST** TO WITHSTAND **THE WORST.**

Product **data sheet**



SOS400MK2

Mounting options:

GRP posts

2 x GRP Posts with or without GRP feet (2 x SOS400FL (with feet) 1540mm length or 2 x SOS400XL (without feet) 2000mm length)

Galvanised post:

1 x galvanised steel post (as shown on left) with polyethylene backplate

(1 x SOS4/7 plus 1 x SOS400/700 Backplate or (1 x SOS4/7 XL plus 1 x SOS400/700 Backplate)

Rail

3 x 316 Stainless steel rail mounting brackets (1 x SOSBRACKET (kit of 3)

Wall

No fixings supplied but cabinet has recesses where four screws can be fitted

Sign mounting options

2 or 4 GRP sign clamps to secure sign to 2 x GRP posts

(2 x SOS400C)

